PRODUCT DATA SHEET



F050-3S4 - 2" MECHANICAL FLOW METER WITH HEAVY DUTY MECHANICAL DISPLAY

The M Series 2" MECHANICAL FLOW METER are suitable for flows between 15-500 L/min (3.96-132.09 GPM), providing highly accurate flow measurement performance. The M Series offers $\pm 1.00\%$ accuracy of true reading in a compact footprint, requiring no flow conditioning and with high pressure and temperature capabilities.

Key features include:

- Cast Aluminium construction
- FKM (Viton) seals
- Maximum flow rate 500 L/min / 132.09 GPM
- Accuracy of ±1.00% of reading
- Exceptional repeatability of ±0.03%
- Temperature up to 80 °C / 176 °F
- 1 point factory calibration as standard, with additional points upon request

SPECIFICATIONS



F050-3S4

	F050-3S4		
Material of construction			
Meter Body	Cast Aluminium		
Rotor	PPS		
Seals	FKM (Viton)		
Design Specifications			
Process Connections	2" NPT Thread [w/ litres mech display]		
Technical Specifications	min	max	
Flow rate < 5cPr > 5cP Non lubricating fluids Operating Temperature Range**	15 3.96 15 3.96 - - -40 -40	500 132.09 500 132.09 500 132.09 80 176	L/min GPM L/min GPM L/min GPM °C °F
Accuracy (±%) Repeatability (±%) Nominal K-Factor	1.00% 0.03% - Pulses/Litre - Pulses/Gallon		

OUTPUT TYPE



HEAVY DUTY MECHANICAL DISPLAY

	Ticary Duty Michanical	
Construction	Aluminium	
IP Rating	IP67	
Тетр	Min: - Max: - °C	
	Min: - Max: - °F	
EX Approvals	-	
	Please refer to instruction manual and certification documentation for product appropriate certification information	
Display		
Digit size (upper/lower)	17mm/6mm	
Accumulated total	✓	
Resettable total	✓	
Preset total	×	
Flow rate	×	
Outputs		
4.20 4. (×	
4-20 mA (passive)	×	
Pulse/Transistor Output	×	
Flow Alarm	×	
Batch Control output	•••	


Heavy Duty Mechanical


<u>macnaught.com</u> Email: <u>meters@macnaught.com</u> Part Number: F050-3S4


PRODUCT DATA SHEET




F050-1S4 S050-1S4 M050-1S4










DISPLAY HEIGHT - A

TYPE 3
MECHANICAL REGISTER - STANDARD





TYPE 4

