



Model	PRL - 25	PRL - 32
Max. Drilling Cap.	25 mm	32 mm
Motor power	1200 W	1300 W
Travel	180 mm	200 mm
Attraction	12000 N	14000 N



Model	DP4113
Drilling Cap.(mm)	13 mm(1/2")
Motor Power	250 W
Spindle Travel(mm)	50
Class of speed	5
Spindle taper	B16
Swing(mm)	210
Table Size(mm)	160x160
Base Size(mm)	290x190
Column Dia.(mm)	ø 46
Height(mm)	580
N.W./G.W.(kgs)	19/20
Packing Size(mm)	430x350x230

Model	DPQ4116
Drilling Cap.(mm)	16 mm(5/8")
Motor Power	550 W
Spindle Travel(mm)	85
Class of speed	16
Spindle taper	MT#2
Swing(mm)	325
Table Size(mm)	ø290
Base Size(mm)	420x250
Column Dia.(mm)	ø 70-72
Height(mm)	980
N.W./G.W.(kgs)	50/52
Packing Size(mm)	780x450x280

Model	DPQ5116
Drilling Cap.(mm)	16 mm(5/8")
Motor Power	550 W
Spindle Travel(mm)	85
Class of speed	16
Spindle taper	MT#2
Swing(mm)	325
Table Size(mm)	ø290
Base Size(mm)	460x272
Column Dia.(mm)	ø 70-72
Height(mm)	1580
N.W./G.W.(kgs)	60/63
Packing Size(mm)	1140x460x280

This documents and its contents are proprietary and confidential and may not be disclosed without express permission in writing.